

**REMARKS**

Claims 1-5, 7-10, 12-14, and 16-19, including amended claims 1 and 12, appear in this application for the Examiner's review and consideration. A marked up version of the amended claims, showing insertions and deletions, is attached as Appendix A. A clean version of the pending claims is attached as Appendix B. No new matter has been entered by these amendments.

**Claim Rejections- 35 U.S.C. § 112**

The Examiner rejected claims 7, 12, and 16 under the second paragraph of 35 U.S.C. § 112 as being indefinite for failing to particularly point out and distinctly claim the subject matter of the invention. In response, claim 1 has been amended to be consistent with dependent claims 7 and 16.

Claim 12 has also been amended to depend from claim 1. In light of these claim amendments, Applicants respectfully submit that the indefiniteness rejection has been overcome.

**Conclusion**

In view of the foregoing, it is believed that all rejections have been overcome and should be withdrawn. Thus, all current claims are submitted to be in condition for allowance, early notice of which would be appreciated. If the Examiner does not agree, then a personal or telephonic interview is respectfully requested to discuss any remaining issues and accelerate the eventual allowance of the claims.

No fee is believed to be due for this submission. Should any fees be required, however, please charge such fee to Pennie & Edmonds LLP Deposit Account No. 16-1150.

Respectfully submitted,



For: Brian M. Poissant

Date February 4, 2003

Brian J. Malm	44,895
For: Brian M. Poissant	28,462

**PENNIE & EDMONDS LLP**  
1667 K Street, N.W.  
Washington, DC 20006

Enclosures

(202) 496-4400

U.S. Application No.: 09/824,838  
Attorney Docket No.: 8932-392

Amendment in Response to September 11, 2002 Office Action  
Examiner James Smith

## Appendix A Marked Up Version of Amended Claims

1. (Amended) A device for securing a screw comprising:  
a longitudinal shank having a central axis and rear and front ends;  
a spindle, located at the front end of the longitudinal shank and concentric to the central axis, having front and rear ends, a substantially polygonal-shaped cross-section with a plurality of rounded edges and a plurality of concave side surfaces, a groove substantially parallel to the central axis, and a borehole coextensive with the groove; and  
a spring wire having top and bottom ends, with the bottom end inserted into the borehole and the top end inserted into the groove,  
wherein the spring wire projects transversely to the central axis across the cross-section when unstressed, the spindle is received into a screwhead aperture of the screw, and the screw is secured into position upon stress to the spring wire, and wherein the groove and the borehole are flush with one of the plurality of rounded edges or one of the plurality of concave side surfaces.
12. (Amended) The device of claim 1[1], wherein the spring wire has a width of 2 mm.

U.S. Application No.: 09/824,838  
Attorney Docket No.: 8932-392

Amendment in Response to September 11, 2002 Office Action  
Examiner James Smith

## Appendix B Clean Version of Pending Claims

1. (Amended) A device for securing a screw comprising:  
a longitudinal shank having a central axis and rear and front ends;  
a spindle, located at the front end of the longitudinal shank and concentric to the central axis, having front and rear ends, a substantially polygonal-shaped cross-section with a plurality of rounded edges and a plurality of concave side surfaces, a groove substantially parallel to the central axis, and a borehole coextensive with the groove; and  
a spring wire having top and bottom ends, with the bottom end inserted into the borehole and the top end inserted into the groove,  
wherein the spring wire projects transversely to the central axis across the cross-section when unstressed, the spindle is received into a screwhead aperture of the screw, and the screw is secured into position upon stress to the spring wire, and wherein the groove and the borehole are flush with one of the plurality of rounded edges or one of the plurality of concave side surfaces.
2. The device of claim 1, wherein the rear end of the longitudinal shank is configured and dimensioned to be received into a motor-driven screwdriver.
3. The device of claim 1, wherein the rear end of the longitudinal shank is configured and dimensioned to be received by a screwdriver.
4. The device of claim 1, wherein the shank has a first diameter and the spindle has a second diameter less than the first diameter.
5. The device of claim 1, wherein the spindle has a hexagonal shape.
7. The device of claim 1, wherein the groove and the borehole are flush with one of the plurality of concave side surfaces.

U.S. Application No.: 09/824,838  
Attorney Docket No.: 8932-392

Amendment in Response to September 11, 2002 Office Action  
Examiner James Smith

8. The device of claim 1, wherein the spring wire is bendable substantially perpendicular to the central axis.
9. The device of claim 1, wherein the top end of the spring wire is fixed in the groove.
10. The device of claim 9, wherein the top end of the spring wire is bonded, soldered, or clamped into the groove.
12. (Amended) The device of claim 1, wherein the spring wire has a width of 2 mm.
13. A method of securing a screw while implanting into a body comprising:
  - providing a screw having an aperture in a screwhead;
  - providing the device of claim 1; and
  - inserting the spindle into the aperture resulting in stress to the spring wire, wherein upon application of the stress, the spring wire holds the screw in a steady position.
14. The method of claim 13, wherein the screw is a bone or pedicle screw.
16. The method of claim 13, wherein the groove and the borehole are flush with one of the plurality of concave side surfaces.
17. The method of claim 13, wherein the spring wire is bendable substantially perpendicular to the central axis.
18. The method of claim 13, wherein the top end of the spring wire is fixed in the groove.

U.S. Application No.: 09/824,838  
Attorney Docket No.: 8932-392

Amendment in Response to September 11, 2002 Office Action  
Examiner James Smith

19. The method of claim 18, wherein the top end of the spring wire is bonded, soldered, or clamped into the groove.